

NH/NJ series

Speed Dryer

			NH-11	NH-12	NH-13	NH-14
Max. working temperature	°C		150	150	150	150
Loading capacity	kg		30	50	75	100
Door leaves			1	1	1	2
Shelves			5	8	8	8
Number of vats			5	8	16	16
Vat dimensions (WxDxH)	mm		396 x 562 x 45	396 x 562 x 45	296 x 562 x 45	396 x 562 x 45
Power	Total electric capacity	kVA	2.35	2.35	4.35	4.35
	Power consumption	kW	2.2	2.2	4.2	4.2
	Heater power	kW	2.0	2.0	4.0	4.0
	Blower power	kW	0.2	0.2	0.2	0.2
	Power supply standard		200 / 220V 50 / 60Hz 3ø			
	Power plug		20A-3P plug with protective ground			
Outer dimensions (WxDxH)	mm		975 x 775 x 1,160	975 x 775 x 1,400	1,245 x 775 x 1,400	1,525 x 775 x 1,440
Chamber dimensions (WxDxH)	mm		410 x 600 x 450	410 x 600 x 690	(310 x 2) x 600 x 690	(410 x 2) x 600 x 690
Weight	kg		145	150	180	195

			NJ-11	NJ-12	NJ-13
Max. working temperature	°C		150	150	150
Loading capacity	kg		100	150	200
Door leaves			2	2	4
Shelves			8	8	8
Number of vats			16	32	32
Vat dimensions (WxDxH)	mm		396 x 562 x 45	296 x 562 x 45	396 x 562 x 45
Power	Total electric capacity	kVA	4.69	8.69	8.69
	Power consumption	kW	4.4	8.4	8.4
	Heater power	kW	4.0 (2.0 x 2)	8.0 (4.0 x 2)	8.0 (4.0 x 2)
	Blower power	kW	0.4 (0.2 x 2)	0.4 (0.2 x 2)	0.4 (0.2 x 2)
	Power supply standard		200 / 220V 50 / 60Hz 3ø		
	Power plug		20A-3P plug with protective ground	30A-3P plug with protective ground	
Outer dimensions (WxDxH)	mm		1,875 x 775 x 1,440	2,415 x 775 x 1,440	2,940 x 775 x 1,440
Chamber dimensions (WxDxH)	mm		(410 x 2) x 600 x 690	(310 x 4) x 600 x 690	(410 x 2) x 600 x 690
Weight	kg		200	250	255

● Specifications are subject to change without notice.